KIK CUSTOM PRODUCTS

SAFETY DATA SHEET

Page **1** of **7**

B-9618

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.

SDS Revision Date: 05-01-2018

	1. PRODUCT & COMPANY IDENTIFICATION					
1.1	Product Name:	KENRA – ARTFORMATION HAIRSPRAY 55%				
1.2	Chemical Name:	Aerosol				
1.3	Synonyms:	ARTFORMATION HAIRSPRAY 55%VOC – B-9618				
1.4	Trade Names:	KENRA – ARTFORMATION HAIRSPRAY 55%				
1.5	Product Uses & Restrictions	Professional and Cosmetic Use				
1.6	Distributor's Name:	KIK Custom Products				
1.7	Distributor's Address:	2030 Old Candler Road, Gainesville, GA 30507 USA				
1.8	Emergency Phone:	CHEMTEL: +1 (703) 527-3887 / +1 (800) 424-9300				
1.9	Business Phone / Fax:	+1 (770) 534-0300 / +1 (770) 534-8954				

2. HAZARDS IDENTIFICATION

2.1	Hazard Identification:	This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the	
		classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia)	
		WARNING! FLAMMABLE AEROSOL. PRESSURIZED CONTAINER: MAY BURST IF HEATED. HIGHLY	
		FLAMMABLE LIQUID AND VAPOR. CAUSES EYE IRRITATION.	
		Classification: Aerosol level 1; Category 2 Flammable aerosol; Eye Irritant. 2	
		Hazard Statements (H): H-223 – Flammable Aerosol. H229 – Pressurized container: may burst if	
		heated. H320 – Causes eye irritation.	
		Precautionary Statement (P): P210 – Keep away from heat, hot surfaces, sparks, open flames and	Y
		other ignition sources. No Smoking. P211 – Do not spray on an open flame or other ignition	
		source. P251 – Do not pierce or burn, even after use. IF IN EYES: Rinse continuously with water for	
		several minutes. Remove contact lenses if present and easy to do – continue rinsing. P337+P313 –	
		If eye irritation persists: Get medical advice/attention. P410+P412 – Protect from sunlight. Do no	
		expose to temperature exceeding 50°C (122 °F). P501 – Dispose of contents/container to licensed	
		and permitted disposal or recycling facility.	

3. COMPOSITION & INGREDIENT INFORMATION							
Substance / Chemical Name(s)	CAS No.	EINECS No.	%	Other			
ETHANOL (SD ALCOHOL 40B)	64-17-5	200-578-6	30-60	Flam. Liq. 2; H225			
DIFLUOROETHANE (R-152a)	75-37-6	200-866-1	30-60	Flam. Gas 1; H220			

			4. FIRST AID MEASURES
4.1	First Aid:	Ingestion:	If ingested, do not induce vomiting! If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.
		<u>Skin:</u>	If irritation occurs & product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with plenty of soap and water. Remove contaminated clothing and wash thoroughly before ruse. If irritation, redness or swelling persists, consult a physician immediately.
		<u>Eyes:</u>	If product get in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Raise and lower eyelid(s) while flushing to ensure thorough irrigation. If problems persist seek immediate medical attention.
		Inhalation:	Remove victim to fresh air and keep comfortable for breathing.
4.2	Effects of Exposure:	Ingestion:	If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression.
		<u>Skin:</u>	May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals upon prolonged or repeated exposure.
		Eyes:	Moderately irritating to the eyes.
		Inhalation:	Vapors of this product may be moderately irritating to the nose, throat and other tissues of the respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion,



SAFETY DATA SHEET

B-9618

			and difficulty breathing. Inhalation of concentrated (e.g., drowsiness, dizziness, headaches, nausea).	apors can cause nervous system depression
.3	Symptoms of Overexposure	Ingestion:	May cause nausea, vomiting and/or diarrhea and cer	tral nervous system depression.
		<u>Skin:</u>	Prolonged contact with skin may result in bleaching a allergic skin reactions (e.g., rashes, welts, dermatitis) overexposure may include redness, itching, and irrita	in some sensitive individuals. Symptoms of
		<u>Eyes:</u>	Overexposure in eyes, may cause redness, itching an Contact may cause mild eye irritation including stingi	
		Inhalation:	Symptoms of overexposure can include coughing, where the breathing.	eezing, nasal congestion, and difficulty
.4	Acute Health Effects:	drowsiness, di	ation to eyes and skin near affected areas. Additionally zziness, headaches and nausea.	
1.5	Chronic Health Effects:	be irritating to	chronic health effects are expected to occur from a sing skin and mucous membrane of the eye and respiratory ome sensitive individuals. May also induce skin sensitiz titis.	system. Overexposure may trigger asthma
1.6	Target Organs:	Eyes, skin, res	piratory system.	
1.7	Medical Conditions Aggravated by Exposure	include irritati Existing derma	nazards may be delayed. Most common symptoms ng properties to eyes, respiratory system and skin. atological conditions (such as eczema) and respiratory ch as bronchial asthma and/or bronchitis) may be	HEALTH1FLAMMABILITY3PHYSICAL HAZARDS0PROTECTIVE EQUIPMENTBEYESSKIN
			5. FIREFIGHTING MEASURES	
.1	Fire and Explosion Hazards:	containers to aerosols are b flammable liqu	ol (NFPA 30B). Aerosols may burst at temperatures abour prevent possible bursting. Aerosols may be projectile ha ursting, stay clear until bursting is complete. Containers uids and/or exposed gases if exposed to the heat of fire. with water until the fire has been extinguished.	zards when bursting. If may rupture and release
5.2	Extinguishing Methods: Firefighting Procedures:	As in any fire, demand_and spray to cool f from fire cont waterway. Fir contained bre	am, CO ₂ , Dry Chemical wear MSHA/NIOSH approved self-contained breathing a full protective gear. Keep containers cool until well after ire-exposed surfaces and to protect personnel. Fight fir rol or dilution from entering sewers, drains, drinking wa efighters must use full bunker gear including NIOSH-app athing apparatus to protect against potential hazardous of products and oxygen deficiencies.	r the fire is out. Use water e upwind. Prevent runoff ter supply, or any natural roved positive pressure self-
			6. ACCIDENTIAL RELEASE MEASUR	EC
5.1	Spills:	Equipment (PI Small spills We combustible n Do not use wa materials (e.g. container. Large spills: Ke release. Isolat	g any spill or leak, individuals involved in spill cleanup m	ust wear appropriate Personal Protective g gloves and protective eyewear. Use a non ict and place into a container for later dispo al. Sweep up material using non-sparking stic container or plastic liner within another ay from spill. Stay upwind and away from s unel out of area. Stop spill or release if it ca
	•	7 1	HANDLING AND STORAGE INFORM	

	KIK CUSTOM PRODU	SAFI	ETY D	ΑΤΑ	SHEE	T			_	e 3 of 7 -9618	
Pr	epared to OSHA, ACC, ANS	SI, NOHSC, WHMIS, 2001/58 & 1	272/2008/E	C Standa	ards SD	S Revision:	1. SD	S Revisio	n Date: (05-01-2018	8
<u> </u>	Storage and Handling:	Use and store in a cool, dry, we sunlight. Avoid temperatures a physical damage. To avoid unit	bove 120 °	F. Keep	away from	n incompati	ble substan	ices. Pro	tect con	tainers fro	
7.3	Special Precautions:	Spilled material may present a							geievei	۷.	
	Special Freeducions.	Spined indeend indy present d	51199118 1102		t unattern			sinpery.			
	8. EXPOSURE CONTROLS & PERSONAL PROTECTION										
3.1	Exposure Limits:		ACG	iH		NOHSC	1		HA	OTHER	
	Ppm (mg/m ³)	Chemical Name(s)	TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
		ETHANOL(SD ALCOHOL 40B)	1000	3000	1000	1800	NF	1000	1900	3300	
		DIFLOROETHANE (R-152a)	1000	NA	1000	NA	NA	NE	NA	NA	
3.2	Ventilation & Engineering Controls	General mechanical (e.g., fans) exhaust ventilation to effective product.								-	
8.3	Respiratory Protection:	No special respiratory protection In instances where dusts of this use only protection authorized Canadian CAS Standard Z94.4-5 States, or Australia.	s product ar by 29 CFR § 93 and appli	e genera §1910.13 icable sta	ated, and r 4, applical andards of	espiratory ble U.S. Sta Canadian I	protection te regulatic Provinces, E	is needed ons, or th C memb	d, e er		
8.4	Eye Protection:	None required under normal co used when handling or using la							:	2	
8.5	Hand Protection:	sensitive individuals. When ha	None required under normal conditions of use. However, may cause skin irritation is some sensitive individuals. When handling large quantities (e.g., ≥ 1 gallon (3.8 L)), wear rubber, nitrile or impervious plastic gloves.								
8.6	Body Protection:	No apron required when handling small quantities. When handling large quantities (e.g., \geq 5 lbs.), eye wash station and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water.									
		9. PHYSICA	L & CH	EMIC	AL PRC	OPERTI	ES				
9.1	Appearance:	Aerosol, clear misty spray of lig									
9.2	Odor:	Citrus/ Fruit, Sweet Fragrance									
9.3	Odor Threshold	NA									
9.4	pH:	NA									
9.5	Melting/Freezing Point	NA									
9.6	Initial Boiling Point/ Boiling Range:	NA									
9.7	Flashpoint:	-30 °F (-34 °C) TCC for propella	nt only: 35.6	5 °F (2 °C) EPA met	hod 1010 (concentrate	e only)			
9.8	Upper/Lower Flammability limits	NA									
9.9	Vapor Pressure:	@ 20 °C (68° F) – Can pressure	not to exce	ed 180 p	sig @ 55 °	C (131 °F) 1	L2.4 bar				
9.10	Vapor Density	>1									
9.11	Relative Density:	0.81-0.85									
	Solubility:	Soluble									
9.13	Partition Coefficient (log Pow):	NA									
9.14	Autoignition Temperature:	NA									
	15 Decomposition NA										
9.15	Temperature.										
		Aerosol at ambient temperatur	e								
		Aerosol at ambient temperatur Evaporation Rate >1: Percent V									
9.16	Viscosity:	Evaporation Rate >1: Percent V			ΕΑCTIN	/ITY					



SAFETY DATA SHEET

Page 4 of 7

B-9618

Pre	epared to OSHA, ACC, ANS	SI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1. SDS Revision Date: 05-01-2018						
10.2	Hazardous Decomposition Products:	Oxides of carbon (CO, CO ₂) and sulfur (SO ₂)						
10.3	Hazardous	Will not occur.						
10.4	Polymerization: Conditions to Avoid	Excessive heat, direct sunlight, flames, heat sources and incompatible substances.						
	Incompatible Substances							
2010								
		11. TOXICOLOGICAL INFORMATION						
11.1	Routes of Entry:	Inhalation: YES Absorption: YES Ingesti YES on:						
11.2	Toxicity Data:	This product was not tested on animals. Toxicology data, found in scientific literature, is available and not presented in this document. Hydrofluorocarbon-152a: LC ₅₀ (inh, 2 h, mouse): 977 g/m ³						
11.3	Acute Toxicity:	See Section 4.4						
11.4	Chronic Toxicity:	See Section 4.5						
11.5	Suspected Carcinogen:	No.						
11.6	Reproductive Toxicity:	This product is not reported to cause reproductive toxicity in humans.						
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.						
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.						
	Teratogenicity:	This product is not report to cause teratogenic effects in humans.						
	Reproductive Toxicity:	This product is not report to cause reproductive effects in humans.						
	Irritancy of Product:	See Section 4.3						
	Indices:	NA						
11.9	Physician Recommendations:	Treat symptomatically.						
		12. ECOLOGICAL INFORMATION						
12.1	Environmental Stability:	There is no specific data available for this product.						
12.2	Effects on Plants & Animals	There is no specific data available for this product.						
12.3	Effects on Aquatic Life:	The product itself has not been tested as a whole. There is no specific data available for this product.						
		13. DISPOSAL CONSIDERATIONS						
13.1	Waste Disposal:	Review current local, state and federal laws, codes, statutes and regulations to determine current status and appropriate disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with local, state and federal laws and regulations. Contact the appropriate agency for specific information. A licensed facility or waste hauler must provide treatment, transport, storage and disposal of hazardous waste.						
13.2	Special Considerations:	U.S. EPA Hazardous Waste – Characteristic – Ignitable (D001)						
		14. TRANSPORTATION INFORMATION						
14.1	49 CFR (GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL < 1.0 L); or						
		CONSUMER COMMODITY, ORM-D (IP VOL \leq 1.0 L) – until 12/31/2020						
14.2	IATA (AIR)	UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL < 0.5 L); or ID8000, CONSUMER COMMODITY, ORM-D (IP VOL < 0.5 I=L)						
14.3	IMDG (OCN):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL < 1.0 L)						
14.4	TDGR (Canadian GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL < 1.0 L); or MARK PACKAGE "LIMITED QUANTITY", "LTD QTY", OR "QUANT LTÉE" OR "QUANTITÉ LIMITÉE"						
14.5	ADR/RID (EU):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL <u><</u> 1.0 L)						
	SCT (MEXICO):	UN1950, AEROSOLES, 2.1 (CANTIDAD LIMITADA, IP VOL <u><</u> 1.0 L)						
14.7	ADGR (AUS):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL <u><</u> 1.0 L)						
		15. REGULATORY INFORMATION						
15.1	SARA Reporting Requirements:	This product does not contain any substance subject to SATA Title III, section 313 reporting requirements.						
	negui cificito.							



SAFETY DATA SHEET

Page **5** of **7**

B-9618

Pr	epared to OSHA, ACC, AN	SI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards S	DS Revision: 1.	SDS Revision Date: 0	5-01-2018			
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inve	ntory.					
15.4	CERCLA Reportable Quantity (RQ):	Ethanol: 2270 kg; 5000 lbs.						
15.5	Other Federal Requirements:	This product complies with the appropriate sections of the (Cosmetics)	Food and Drug Adm	ninistration's 21 CFR Su	ubchapter G.			
15.6	Other Canadian Regulations:	This product has been classified according to the hazard cri of the information required by the CPR. The components o DSL/NDSL. None of the components of this product are list WHMIS Class B5 (Flammable Aerosol)	f the product are lis	sted on the				
15.7	State Regulatory Information:	<u>Ethanol</u> is found on the following state criteria lists: Florida Substances List (MA), Pennsylvania Right-to-Know list (PA), Right-to-Know List (NJ). <u>Difluoroethane</u> can be found on the following state criteria No other ingredients of this product, present in a concentra state criteria lists: California Proposition 65 (CA65), Delawa Substances List (FL), Massachusetts Hazardous Substances I Hazardous Substances List (MN), New Jersey Right-to-Know Pennsylvania Right-to-Know List (PA), Washington Permissil List (WI).	Minnesota Hazardo lists: MA and NJ. ation of 1.0% or gre re Air Quality Mana List (MA), Michigan y List (NJ), New York	ous Substances List (M ater, are listed on any gement List (DE), Flori Critical Substances Lis Hazardous Substance	N), New Jersey of the following da Toxic t (MI), Minnesota s List (NY),			
15.8	Other Requirements:	The primary components of this product are listed in Annex <u>Ethanol:</u> Flammable (F). <u>Risk Phrases</u> [®] : 11 – Flammable. <u>Si</u> reach of children. Keep container tightly closed. Keep awa	afety Phrases (S): 2-	-7-16 – Keep out of	×			
		16. OTHER INFORMAT	ION					
16.1	Other Information:	WARNING! FLAMMABLE AEROSOL. PRESSURIZED CONTA AND VAPOR. CAUSES EYE IRRITATION. Keep away from he sources. No Smoking. Do not spray on an open flame or ot Avoid breathing vapor/spray. Wash thoroughly with soap a Wear eye protection. Protect from sunlight. Do not expose Remove person to fresh air and keep comfortable for breat minutes. Remove contact lenses if present and easy to do. advice/attention. KEEP OUT OF REACH OF CHILDREN.	INER: MAY BURST eat, hot surfaces, sp ther ignition source. and water after han to temperature ex hing. IF IN EYES: Ri	oarks open flames and Do not pierce or burr dling. Use only in a we ceeding 50 °C (122 °F) inse cautiously with wa	other ignition n, even after use. ell ventilated area. . IF INHALED: ater for several			
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.						
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the base of KIK Custom Product's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or complete=ness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.						
16.4	Prepared By:	KIK Custom Products 2030 Old Candler Road Gainesville, GA 30507 USA Tel: +1 (770) 534-0300 Fax: +1 (770) 534-8954 http://www.kikcorp.com	K	IK JSTOM PRO	DUCTS			



